

SD8030I-FTVI

Motorized HDCVI camera 240°/s
1080p (25FPS)
1/2.8" Progressive Scan CMOS
IR LED range 120m
Optical Zoom 30X (4~120 mm)
Suitable for exterior IP66



Safire
HDTV Speed dome camera
High Speed 240°/segundo
30X Optical zoom - 16X Digital zoom
1/2.8" Progressive Scan CMOS
HD 1080P (1920x1080)
HDTV and CVBS output
4.0~120.0 mm Varifocal lens
0 Lux - IR Range 120 m
IR Cut
Pelco P/D protocols supported
OSD Menu
Weatherproof IP66
Bracket not included (see compatible brackets)

Specifications

Brand	SAFIRE
Image sensor	1/2.8" Progressive Scan CMOS
Resolution	1080p (1920x1080) at 25 FPS
Video output	1x BNC formato HDTVI / 1x BNC formato CVBS
Minimum illumination	0.05 Lux (colour) / 0.005 Lux (B/N)
Infrared lighting	Automatic IR LED's, range 120 metres
Lens	Varifocal 4.0 – 120.0 mm (Optical Zoom 30X)
Digital zoom	16 X
Electronic shutter	1/1s–1/10,000s
Day / Night	Removable mechanical ICR filter
Noise reduction	3D-NR
Gain Control	Auto / Manual
Backlight compensation	BLC / DWDR
White balance	Auto, ATW, Interior, Exterior, Manual
Privacy masks	Up to 8 areas
Pan/Tilt Range	Horizontal: 0°–360°, Vertical: -15°–90° auto flip 180°
Manual speed	Horizontal: 0.1° ~160°/s, Vertical: 0.1° ~120°/s
Speed between Presets	Horizontal: 240° /s, Vertical: 200° /s
Preset positions	256 preset, 4 auto pattern, 8 auto tour, auto pan, auto scan
Communication	RS485, Pelco P / Pelco D / SAFIRE
Audio	No
Alarms	No
Power supply	AC 24 V / 2.2 A
Temp. operation	-30° C ~ +65° C
Degree of protection	IP66 / Surges 4000V
Dimensions (without support)	354 mm (H) x 220 (Ø) mm
Weight (without support)	4500 g