

SF-DM832ZWU-F4N1

Safire ULTRA Range

Ultra Low Light

2 MP high performance CMOS

2.8~12mm motorised auto-focus lens

Smart IR Matrix range 40 m

3DNR, WDR



Safire

HDTVI, HDCVI, AHD and Analogue dome camera

ULTRA Range

High Performance CMOS

HD 1080P (1920x1080)

Output 4in1

2.8 motorised lens - 12 mm

0 Lux

Ultra Low Light

Smart IR EXIR range 40 m

3DNR

WDR

IR Cut

Weatherproof IP67

Specifications

Range	1080p ULTRA
Image sensor	2 MP High Performance CMOS
Resolution	HD 1080p (1920x1080) at 25 FPS
Video output	1 x BNC switchable between HDTV / HDCVI / AHD / CVBS
Minimum illumination	0.005 Lux
Infrared lighting	0 Lux / SMART IR EXIR LEDs (40 m)
Basic functions	OSD menu (remote), Day/Night with IR-CUT (ICR), ATR
Configurable OSD functions	DWDR, 2D/3D-NR, AWB, ATW, HLC, BLC, AGC, AF, Sense-UP,AE, AWB, AGC
Lens	2.8 motorised lens - 12 mm
Power supply	DC 12 V / 1000 mA
Degree of protection	Weatherproof IP67
Temp. operation	-40° C ~ +60° C
Dimensions	111 (D) x 145 (Ø) mm
Weight	890 g