

SF-IPSD5104IAWH-4

4 MP Motorised IP Camera
1/3" Progressive Scan CMOS
Compression H.265+/ H.265 /
H.264+/ H.264
2.8~12 mm Lens (4X) Auto Iris
IR LEDs Range 20 m
WEB, CMS Software, Smartphone
and NVR



Safire
PTZ IP Camera
Average speed 100°/segundo
4X Optical zoom
1/3" Progressive Scan CMOS
4 Megapixel (2560x1440)
2.8~12mm Varifocal Lens
IR Range 20 m
Compression H.265+/H.265/H.264+/H.264
RJ-45 10/100 BaseT
PoE 802.3af
Weatherproof IP66
IR Cut
WDR
Audio
SD card recording
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible

Specifications

Brand	SAFIRE
Image sensor	1/3" Progressive Scan CMOS
Resolution	4 Megapixel (2688x1520)
Minimum illumination	0.005 Lux (color) / 0.001 Lux (B/N) @ F1.6
Infrared lighting	IR LEDs (20 m)
Compression	H.265+/ H.265 / H.264+/ H.264
Lens	Varifocal 2.8~12 mm (Optical Zoom 4X)
Digital zoom	16X
Electronic shutter	1/1s~1/30,000s
Day / Night	Removable mechanical ICR filter
Image improvements	BLC, HLC, WDR, 3D-NR, AGC, AWB, MD, Privacy Masking, ROI, ANR
Video analysis	VCA: Line crossing Intrusion in area Audio exception Abandoned object
Pan/Tilt Range	Horizontal: 0°~330°, Vertical: 0°~90° auto flip
Manual speed	Horizontal: 0.1° ~ 100°/sec, Vertical: 0.1° ~100°/s
Speed between Presets	Horizontal: 100° /s, Vertical: 100° /s
Preset positions	300 preset
Internal memory	MicroSD card, Max 256 GB
Audio	1 input (Line In) / 1 output (Line Out)
Alarms	No
PTZ Control	Through network access
Network interface	Ethernet 10 / 100 BaseT
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI
Power supply	DC 12 V / 1.5 A, PoE IEEE802.3af
Temp. operation	-20° C ~ +60° C
Degree of protection	Waterproof IP66 / Overvoltages 4000V / Anti-vandal IK10
Dimensions (without support)	101.7 mm (H) x 130.7 (Ø) mm
Weight (without support)	530 g