

SW0908POE-120W

Switch PoE

8 PoE port(s) + 1 Up-link port(s)

Speed 10/100Mbps

25.5W per port / Total maximum

120W

CCTV Mode: up to 250m cable length

Norm IEEE802.3at (PoE) / af (PoE+)



SAFIRE 9 port desktop Switch with 8 PoE port(s).

Quick and easy network connectivity for up to 8 Ethernet devices and also 1 Up-link RJ45 10/100Mbps port(s) for inter-connectivity con other network resources. Ports 1 to 8 support Power over Ethernet (PoE) and are able to provide electrical power over the same network cable to a camera or other PoE device.

It has a table of MAC addresses 1 K and supports automatic learning and expiration of MAC addresses (Auto-Learning and Auto-aging). Supports Auto-MDI/MDI-X. Protocols IEEE 802.3 10 Base-T / 100 Base-TX.

The Power over Ethernet (PoE) power supply of this switch meets the IEEE 802.3at (PoE+) and IEEE 802.3af (PoE) standards, and self-determining the power needs of the powered device, up to 25.5 W per port and a total of 120 W. With CCTV mode which significantly increases the cable length to 250 metres @ 10Mbps.

Specifications

Interface	8 RJ45 PoE port(s) + 1 Up-link port(s)
Port speed	10/100 Mbps
MAC address table	1 K
Power supply	25.5 W per port (120 W for the entire device)
PoE features	According to norm IEEE 802.3at PoE+ / IEEE 802.3af PoE
Power supply	DC 48-56 V / 2.5 A
Operating temperature	0° C - 55° C
Dimensions / Weight	105 (D) x 28 (H) x 220 (W) mm / 600 g