

SF-HTVR8216A-HEVC

Safire 5n1 H.265+ Recorder

Save space and bandwidth

16 CH HDTVI / HDCVI / AHD / CVBS

/ 2 IP

5 Mpx/4 Mpx/3 Mpx (

HDMI 4K, VGA and BNC (CVBS)

output

(16/4) Alarms | 4Ch audio / 2 HDD



Safire

DVR 5n1

16Ch video HDTVI/HDCVI/AHD/CVBS / 2 IP (extra) / 4Ch audio

H.265+/H.265/H.264+/H.264

Resolution per channel: 5Mpx (10FPS) or 4Mpx (15FPS) or 3Mpx (18FPS) on TVI or 1080p (25FPS) in the rest of HD technologies.

PTZ Control (RS485/Coaxial)

Alarms

HDMI 4K, VGA & CVBS Outputs

Remote control - Mouse

Space for 2 HDD

Specifications

Brand	SAFIRE
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	16 Channels BNC, (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	16 Channels from BNC and 2 Channels IP (6Mpx)
Video outputs	1 HDMI 4K, 1 VGA, 1 BNC (CVBS) Independent
Audio inputs	4 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Video / audio compression	H.265+ / H.265 / H.264+ / H.264 / G.711u
Display resolution	4K (3840x2160), 2K (2560x1440), 1920x1080, 1280x1024, 1280x720, 1024x768
Recording resolution	4K / 5Mpx / 4Mpx / 3Mpx / 1080p / 1080p Lite / 720p / WD1 / 4CIF / VGA / CIF
Main Stream coding	4K (8 FPS) / 5Mpx (12 FPS) / 4Mpx (15 FPS) / 3Mpx (18 FPS) in TVI / 1080p / 720p / VGA / WD1 / 4CIF / CIF (1~25FPS)
Extra Stream coding	WD1 / 4CIF / CIF (25 FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	16 inputs / 4 relay
Video analysis	VCA: Tripwire Area intrusion Audio exception
Recording method	Manual, programmed, motion detection, alarm
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network
Internal memory	2 SATA HDD 3.5" of up to 8 TB (not included)
Communication	RS485 (PTZ) / 2 x USB (Mouse and backup) / Remote control / RJ45 (Ethernet)
Remote access	Web browser, Smartphone App and Safire Control Center CMS Software
Power supply	DC 12 V / 25W
Dimensions / Weight	48 (H) x 380 (W) x 320 (D) mm / 2.0 Kg